

## Models 800 ADV & 800C ADV

### DOOR DIMENSION CHART

Please be advised that the dimensions provided below are approximations based on standard offerings. If options are added or sideroom and headroom clearances are tight on your projects, please be sure to work with the factory for the most accurate data based on your jobs needs.  
800 ADV & 800C ADV Face of Wall Mounted

MODEL	SLAT	MAX WIDTH	STD FRONT	STD BACK	OPTIONAL FRONT	R-VAL.	STC RATING
800 ADV	#14	Up to 15'4"	22-ga. steel	N/A	20-, 18-ga. Steel or 20-, 22-ga. Stainless steel, or 16-ga. (.050") B&S aluminum	N/A	N/A
800C ADV	#34	Up to 20'0"	22-ga. steel	24-ga. Steel	20-, 18-ga. steel or 22-, 20-ga. Stainless steel or 16-ga. (.050") B&S aluminum	7.7	22

Slats are galvanized and painted or stainless steel (SS) or aluminum.

### Headroom Clearance Dimensions

SLAT	OPENING HEIGHT	DIMENSION A
#14	<10'0"	18.5"
#14	10'1" – 15'0"	20"
#14	15'1" – 20'0"	22"
#34	<6'0"	18.5"
#34	6'1" – 9'0"	20"
#34	9'1" – 14'0"	22"
#34	14'1" – 20'0"	*N/A

\*Based on the door opening width of 10'0" wide

## **Models 800 ADV & 800C ADV DOOR DIMENSION CHART**

### **Sideroom Clearance Dimensions**

Dimension C – Drive Side: 18”

Dimension D – Non-Drive Side: 12”

### **Sideroom and Headroom**

This door system requires a minimum of 12” on the non-drive side (9” if the cover is not used) and no less than 18” on the drive side (no less than 16” if the cover is not used). Base headroom requires a minimum of 15” up to 28” depending on head plate size. Add 2.5” for a hood.